

CircumMaxx


Circumferential agitator against sinking and floating layers

CircumMaxx is an intelligent and substrate flexible agitator. The unique combination of agitator direction and power enables a three-dimensional mix. Consequently, both sinking and floating layers can be treat preventively and dissolve safely with minimal expenditure of energy.

In order to respond to changing conditions, modern fermentation plants' agitators need to adjust flexibly. CircumMaxx is automatically and flexibly adjustable to changing situations. The proven pivoting agitator nozzletechnique, which is combine with an automatic 360° position encoder, detects all directions in the fermenter.

In conjunction with intelligent controlling technology, it is possible to implement a variety of mixing-scenarios, which can integrated specifically into the procedure. This ensured an energy-optimised mixing of the complete content. The microorganisms will be distributed ideally and reduce the residual gas potential.

CircumMaxx can installed in any type of container. The well thought-out construction allows easy installation also on existing containers.



Technical dataMixing in three-dimensional space

| Length | Inside: ca. 2 000 mm Outside: ca. 3 000 mm |
|-----------------|--|
| Material | galvanized steel stainless steel (optional) |
| Drive | electric drive: 15 to 30 kW tractor drive: up to 150 kW |
| Agitator nozzle | 30° at Ø 600 mm 360° free swiveling traversable with stepper motor |
| Control | optional pushbutton r/l in steps of 5° or by integration in MSR |
| Propeller | Ø ca. 560 mm |
| Sealing | ca. 50 m submersible |
| Embedding | ground foundation No power transmission onto container wall |

Subject to technical changes!

Your advantages at a glance:

Powerful nozzle technology

- Position of the nozzles are automatically variable and adjustable
- Driven by an electric motor or 150 kW tractor operation
- Termination system for all types of liquid manure containers can achieved

Dynamic stirring in 3-D

- Any layer in the fermenter can steered specifically
- Flexible use for any container geometry
- Variable even in substrate flexibility

CircumMaxx – simple and robust

- Broad application possibilities
- Safe operation, redundant drive
- Simple installation and maintenance, visible technology
- intelligent substrate-flexible mixing

Variable stirring positions

By varying

- number of agitators
- driving power of the agitators
- nozzle position
- synchronization of the agitators
- ✓ automatic program selection it is possible to control any position in the fermenter. Furthermore, combinations with additional agitators are also possible.

Should you need further information about our innovative products?
Please do not hesitate to contact us.
We will be pleased to advise you!



Energie-Anlagen Röring GmbH Rudolf-Diesel-Straße 3b - 48691 Vreden



Phone: + 49 2564 394939-0 Fax: + 49 2564 394939-49 info@energieanlagen-roering.de www.energieanlagen-roering.de